

## How to Order

WFC	Q3	105	K	225	000	B	R
Series	Voltage 1.	Capacitance 2.	Capacitance Tolerance 3.	Pitch 4.	Lead Length 5.	Packing 6	Pb 7

### 1, Voltage

Code	1H	1J	2A	2C	2D	2E	2G	2S	2T	2J	2V	3A	4M	3C	3D
VDC	50V	63V	100V	160V	200V	250V	400V	450V	520V	630V	760V	1000 V	1500 V	1600 V	2000 V
Code	P1	P2	Q1	Q2	Q3	G2	S2	H2	U1	65	V1	Other Voltage Code, Please consult WEET !			
VAC	250 VAC	275 VAC	300 VAC	305 VAC	310 VAC	400 VAC	450 VAC	500 VAC	600 VAC	650 VAC	700 VAC				

Note: Letter and number indicate VAC, Number and Letter indicate VDC. For example, A2=100VAC, 2A=100VDC

### 2, Capacitance

Code	100	101	102	103	104	105	106	223	474
Values	10pF	100pF	1000pF	0.01uF	0.1uF	1uF	10uF	0.022uF	0.47uF

### 3, Capacitance Tolerance

Code	F	G	E	J	K	M
Tolerance	±1%	±2%	±3%	±5%	±10%	±20%

### 4, Pitch

Code	035	040	050	075	100	150	200	225	275	000
Pitch (mm)	3.5	4.0	5.0	7.5	10.0	15.0	20.0	22.5	27.5	Axial

### 5, Lead Length

Code	000	035	040	050	075	100	150	200	225	275	350	550
Length (mm)	Standard	3.5	4.0	5.0	7.5	10.0	15.0	20.0	22.5	27.5	35	55

### 6, Packing

Code	A	B	R
Packing	Ammo	Bulk	Tape Reel

### 7,Pb

Code	R
Pb	RoHS

